

BX

BX1860/BX2360 BX2660/BX25

SPECIFICATIONS

Specifications

Model		BX1860	BX2360	BX2660	BX25
Engine					
Type		Liquid-cooled, 3-cylinder diesel			
Model		Kubota D722	Kubota D902	Kubota D1005	Kubota D902
Engine gross HP at 3200 rpm	HP (kW)	18.0 (13.4)	23.0 (17.2)	25.5 (19.0)	23.0 (17.2)
PTO horsepower at 3200 rpm	HP (kW)	13.7 (10.2)	17.7 (13.2)	19.5 (14.5)	17.7 (13.2)
Displacement	cu.in. (cc)	43.9 (719)	54.8 (898)	61.1 (1001)	54.8 (898)
Fuel tank capacity	gal. (l)	6.6 (25)			
Drive train					
Transmission		HST, High-Low gear shift (2 forward / reverse)			
Drive method		2WD and 4WD selection			
Brakes		Wet disc			
PTO		Live independent, wet hydraulic clutch			
Rear		STD (540rpm)			
Mid		STD (2500rpm)			
Hydraulics					
Pump output	gpm (l/min.)	6.3 (24)			
3-point hitch		Category I			Optional
Lift capacity @ 24" behind pin	lbs. (kg)	670 (300)			
Steering		Hydrostatic Power Steering			
Tire size					
Front	Turf/Bar/Industrial	16x7.5-8 / 16x7.5-8 / N.A.	18x8.5-10 / 18x8.5-10 / 18x8.5-10		18x8.5-10 / N.A. / 18x8.5-10
Rear	Turf/Bar/Industrial	24x12-12 / 24x12-12 / N.A.	26x12-12 / 26x12-12 / 26x12-12		26x12-12 / N.A. / 26x12-12
Traveling speeds at rated engine rpm (Turf)					
Forward	mph (km/h)	0-7.8 (0-12.5)		0-8.4 (0-13.5)	
Reverse	mph (km/h)	0-5.7 (0-9.2)		0-6.2 (0-10.0)	
Dimensions					
Length with 3-point hitch	in. (mm)	92.1 (2340)		95.5 (2425)	
Width (w/ turf tire)	in. (mm)	44.5 (1130)			
Height with ROPS	in. (mm)	69.4 (1762)	70.4 (1787)		85.4 (2170)
Wheelbase	in. (mm)	52.8 (1340)		55.1 (1400)	
Ground clearance (front axle)	in. (mm)	9.0 (230)		8.7 (220)	
Tread	Front	34.6 (880)		36.6 (930)	
	Rear	32.2 (820)			
Turning radius (w/o brake)	feet (m)	7.2 (2.2)		7.5 (2.3)	
Tractor weight	lbs. (kg)	1255 (570)	1322 (600)	1389 (630)	1542 (700)

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Roll Over Protective Structure (ROPS) and seat belt in almost all applications.

*Foldable ROPS available on BX25 only. *The loader and backhoe come standard on the BX25 model.

BX

BX1860/BX2360 BX2660/BX25

SPECIFICATIONS

Model

Lift capacity (pivot pin, max. height)	lbs. (kg)	745 (338)
--	-----------	-----------

Model

	lbs. (N)	1936 (8610)
	lbs. (N)	1171 (5209)
om swing mechanism		One cylinder
Shipping weight (with 12" bucket)	lbs. (kg)	617 (280)
Transport height	in. (mm)	67.7 (1719)
Loading height	ft. (mm)	5' (1533)
Digging depth	ft. (mm)	6'1" (1842)
Swing pivot to rear axle center line	in. (mm)	28.6 (726)
Reach from swing pivot	ft. (mm)	8'7" (2612)
Bucket rotation	degrees	180
Swing arc	degrees	140
Angle of departure	degrees	20.1